

DERWENT-ACC-NO: 1991-179326
DERWENT-WEEK: 199125
COPYRIGHT 1999 DERWENT INFORMATION LTD

TITLE: Electrostatic delta-phi micro-lens for low energy
particle beams - used
in electron- or ion-microscopes

INVENTOR: FINK, H; SCHMID, H ; STOCKER, W ; FINK, H W

PATENT-ASSIGNEE: INT BUSINESS MACHINES CORP[IBMC], IBM
CORPNESS MACHINES
CORP[IBMC]

PRIORITY-DATA: 1989EP-0810951 (December 13, 1989)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAGE
PAGES	MAIN-IPC	
EP 432337 A	June 19, 1991	N/A
000	N/A	
DE 68917310 E	September 8, 1994	N/A
000	H01J 037/12	
EP 432337 B1	August 3, 1994	E
007	H01J 037/12	
JP 03194837 A	August 26, 1991	N/A
000	N/A	
US 5059804 A	October 22, 1991	N/A
000	N/A	

DESIGNATED-STATES: DE FR GB DE FR GB

CITED-DOCUMENTS: 2.Jnl.Ref; 02Jnl.Ref

APPLICATION-DATA:

PUB-NO	APPL-DESCRIPTOR	APPL-NO
APPL-DATE		
EP 432337A	N/A	1989EP-0810951
December 13, 1989		
DE68917310E	N/A	1989DE-0617310
December 13, 1989		
DE68917310E	N/A	1989EP-0810951
December 13, 1989		

DE68917310E	Based on	EP 432337
N/A		
EP 432337B1	N/A	1989EP-0810951
December 13, 1989		
JP03194837A	N/A	1990JP-0313005
November 20, 1990		
US 5059804A	N/A	1990US-0607175
October 31, 1990		

INT-CL (IPC): H01J037/12; H01J049/42

ABSTRACTED-PUB-NO: EP 432337A

BASIC-ABSTRACT: A Delta-Phi microlens for low energy particle beams, combined for operation with a source of particles, i.e. a sharply pointed tip, and comprising at least 2 metal foils arranged in close proximity with the tip, and each having a hole exactly aligned with the axis of the tip. One of the metal foils serves as a substrate plate, and the second foil is coated onto at least part of that surface of the substrate plate which is facing away from the tip. The materials of the 2 metal foils are chosen such that in combination their work function difference (delta-phi) is greatest.

Pref. the material of the substrate plate is a transition metal, and more pref. is an alloy of 2 or more transition metals, while the material of the second foil is from groups IA and IIA.

USE/ADVANTAGE - Electrostatic microlens for low energy particle beams for use in electron or ion microscopes.

ABSTRACTED-PUB-NO: EP 432337B

EQUIVALENT-ABSTRACTS: Delta-Phi microlens for low-energy particle beams, comprising at least two meal foils (3,4) each having a hole (2) aligned with each other and to become aligned with the beam axis, characterized in that a first one of said metal foils (3,4) serves as a substrate plate (3), that a

second one (4) of said metal foils is coated onto at least part of a surface of said substrate plate (3), and that the materials of said first and second metal foils (3,4) are chosen to get a difference in work function ($\Delta\phi$) in order to deflect the particles.

US 5059804A

Delta-pin microlens for use in electron or ion microscopes has a sharply pointed tip (1), as source of particles, aligned with a small hole in a thin metal foil (3), e.g. 1 mm thick. A layer (4) of metal different from the foil is coated on the side facing away from the tip, with a thickness, e.g. of 100nm. Combined materials of the foil and coating have a work function difference of about 3 eV.

ADVANTAGE - Insulating spacings between lens elements are not required.
@(4pp)@

CHOSEN-DRAWING: Dwg.1/1 Dwg.1/1

TITLE-TERMS:
ELECTROSTATIC DELTA PHI MICRO LENS LOW ENERGY PARTICLE BEAM
ELECTRON ION
MICROSCOPE

DERWENT-CLASS: L03 S03 V05

CPI-CODES: L03-H04C; L03-H04D;

EPI-CODES: S03-E06B; V05-F03;

SECONDARY-ACC-NO:
CPI Secondary Accession Numbers: C1991-077371
Non-CPI Secondary Accession Numbers: N1991-137425